

15 MVL



SPECIFICATIONS

Driveable Vertical Mast Lift

Key Specs

- Platform Height: 4.71 m / 15.5 ft
- Machine Width: 0.75 m / 2.5 ft

Key Features

- Five platform options with exclusive “Quick Change” mountings for one-minute change-outs
- Exclusive Point & Go® single joystick control operates drive and steer, and lift and lower
- Rigged mast for operator comfort and stability





SPECIFICATIONS

15 MVL

Dimensional Data

Wheel Size - Front Caster	20 x 6 cm
Ground Clearance	0.05 m / 2 in.
Ground Entry Height	0.46 m / 1 ft 6 in.
Machine Height	1.98 m / 6.5 ft
Machine Length	1.36 m / 4.5 ft
Machine Width	0.75 m / 2.5 ft
Platform Dimension A	0.66 m / 2.2 ft
Platform Dimension B	0.66 m / 2.2 ft
Platform Height	4.71 m / 15.5 ft
Wheel Size - Rear	32 x 10 cm
Tire Size	N/A

Reach Specifications

Platform Height	4.71 m / 15.5 ft
Working Height	6.71 m / 22 ft

Performance Data

Drive Speed - Platform Elevated	0.80 km/h / 0.5 mph
Drive Speed - Platform Lowered	5.40 km/h / 3.4 mph
Drive System	4 Brush Direct Electric
Gradeability	20 %
Maximum Drive Height	4.71 m / 15.5 ft
Maximum Lift Height	4.66 m / 15.3 ft
Platform Capacity	230 kg / 5071 lb

General Specifications

Machine Weight (ANSI Export and CSA)	1055 kg / 2325.9 lb
--------------------------------------	---------------------

Power Source

Batteries	100 A/hr AGM (x 2)
-----------	--------------------