

1930 ES



SPECIFICATIONS

Electric Scissor Lift

Key Specs

- Platform Height: 5.72 m / 18.8 ft
- Machine Width: 0.76 m / 2.5 ft
- Working Height: 7.72 m / 25.3 ft

Key Features

- Quieter, cleaner operation for a variety of environments
- Electric drive and integrated components with only two hydraulic hoses and four hydraulic fittings on the entire machine will keep you on the job longer and reduce your operating costs by reducing chances for leaks and service calls
- Narrow width fits through most standard doorways and tight aisles





SPECIFICATIONS

1930 ES

Power Source

Batteries	4 x 6V, 220 A-h
Charger	20 A automatic

General Specifications

Brakes	Electric, Friction
Capacity - Hydraulic Reservoir	4.73 L / 1.2 gal.
Ground Bearing Pressure	8.65 Kg/cm ²
Hydraulic Pump	Fixed Displacement Gear
Machine Weight (ANSI Export and CSA)	1230 kg / 2711.7 lb
Machine Weight	1506 kg / 3320.2 lb

Performance Data

Turning Radius - Inside	0 m / 0 ft
Drive Speed - Platform Elevated	0.80 km/h / 0.5 mph
Drive Speed - Platform Lowered	4.80 km/h / 3 mph
Drive System	24V Electric
Gradeability	25 %
Lift Time	20 sec.
Lower Time	30 sec.
Maximum Drive Height	5.72 m / 18.8 ft
Maximum Lift Height	5.72 m / 18.8 ft
Platform Capacity - Extension	120 kg / 264.6 lb
Platform Capacity - Unrestricted	230 kg / 507.1 lb
Turning Radius - Outside	1.75 m / 5.7 ft

Dimensional Data

Ground Clearance	0.09 m / 4 in.
Machine Height	2.02 m / 6.6 ft
Machine Height - Rails Folded	1.59 m / 5.2 ft
Machine Length	1.87 m / 6.1 ft
Machine Width	0.76 m / 2.5 ft
Platform Dimension A	0.76 m / 2.5 ft
Platform Dimension B	1.87 m / 6.1 ft
Platform Extension Length	0.90 m / 3 ft
Platform Height	5.72 m / 18.8 ft
Platform Height - Lowered	0.89 m / 2.9 ft
Platform Railing Height	1.10 m / 3.6 ft
Tire Size	32 x 10 cm
Wheelbase	1.60 m / 5.2 ft

Reach Specifications

Platform Height	5.72 m / 18.8 ft
Working Height	7.72 m / 25.3 ft