



## Specifications

| MODELS  | AWP™-36S                                 |                | AWP™-40S                                 |                |
|---|--|----------------|--|----------------|
| MEASUREMENTS                                  | US                                       | Metric         | US                                       | Metric         |
| Working height*                               | 42 ft 5 in                               | 13.10 m        | 46 ft 4 in                               | 14.29 m        |
| Platform height                               | 36 ft 5 in                               | 11.10 m        | 40 ft 4 in                               | 12.29 m        |
| <b>A</b> Height - stowed (Standard)           | 9 ft 1.5 in                              | 2.78 m         | 9 ft 1.5 in                              | 2.78 m         |
| stowed (RT)                                   | —  | —              | —  | —              |
| <b>B</b> tilted back** (Standard)             | 6 ft 3.5 in                              | 1.92 m         | 6 ft 6 in                                | 1.98 m         |
| <b>C</b> Length - stowed (Standard)           | 4 ft 7 in                                | 1.40 m         | 4 ft 8 in                                | 1.42 m         |
| stowed (RT)                                   | —  | —              | —  | —              |
| <b>D</b> Length - tilted back**               | 9 ft 9 in                                | 2.97 m         | 9 ft 9 in                                | 2.97 m         |
| <b>E</b> Width (Standard)                     | 2 ft 5 in                                | .74 m          | 2 ft 5 in                                | .74 m          |
| Width (RT)                                    | —  | —              | —  | —              |
| <b>PRODUCTIVITY</b>                           |  |                |  |                |
| Lift capacity                                 | 350 lbs                                  | 159 kg         | 300 lbs                                  | 136 kg         |
| <b>ANSI/CSA:</b>                              |  |                |  |                |
| <b>F</b> Outrigger footprint (l/w) (Standard) | 6 ft 11 in/6 ft 3 in                     | 2.1/1.9 m      | 7 ft 5 in/6 ft 9 in                      | 2.26/2.06 m    |
| <b>G</b> Outrigger footprint (l/w) (RT)       | —  | —              | —  | —              |
| Corner access*** (Standard)                   | 2 ft 5 in                                | .74 m          | 2 ft 7 in                                | .79 m          |
| <b>H</b> Corner access*** (RT)                | —  | —              | —  | —              |
| Wall access front/side (Standard)             | 1 ft 2 in/2 ft 1 in                      | .36/.64 m      | 1 ft 3 in/2 ft 4 in                      | .38/.71 m      |
| <b>I</b> Wall access front/side (RT)          | —  | —              | —  | —              |
| <b>CE/AUS/PB Indoor:</b>                      |  |                |  |                |
| Outrigger footprint (l/w) (Standard)          | 6 ft 11 in/6 ft 3 in                     | 2.12/1.91 m    | 7 ft 5 in /6 ft 9 in                     | 2.26/2.06 m    |
| <b>F</b> Outrigger footprint (l/w) (RT)       | —  | —              | —  | —              |
| Corner access*** (Standard)                   | 2 ft 5 in                                | .74 m          | 2 ft 7 in                                | .79 m          |
| <b>H</b> Corner access*** (RT)                | —  | —              | —  | —              |
| Wall access front/side (Standard)             | 1 ft 2 in/2 ft 1 in                      | .36/.64 m      | 1 ft 3 in/2 ft 4 in                      | .38/.71 m      |
| <b>I</b> Wall access front/side (RT)          | —  | —              | —  | —              |
| <b>CE/AUS/PB Outdoor:</b>                     |  |                |  |                |
| Outrigger footprint (l/w) (Standard)          | 11 ft 7 in/10 ft 11 in                   | 3.53/3.33 m    | 12 ft 9 in/12 ft 1 in                    | 3.89/3.68 m    |
| <b>F</b> Outrigger footprint (l/w) (RT)       | —  | —              | —  | —              |
| Corner access*** (Standard)                   | 3 ft 4 in                                | 1.02 m         | 3 ft 8 in                                | 1.12 m         |
| <b>H</b> Corner access*** (RT)                | —  | —              | —  | —              |
| Wall access front/side (Standard)             | 3 ft 4 in/4 ft 4 in                      | 1.02/1.32 m    | 3 ft 8 in/5 ft                           | 1.12/1.52 m    |
| <b>I</b> Wall access front/side (RT)          | —  | —              | —  | —              |
| <b>Platform Dimensions: (l/w/h)</b>           |  |                |  |                |
| Standard                                      | 27/26/44.75 in                           | .69/.66/1.14 m | 27/26/44.75 in                           | .69/.66/1.14 m |
| Gated standard                                | 27/26/44.75 in                           | .69/.66/1.14 m | 27/26/44.75 in                           | .69/.66/1.14 m |
| Gated narrow                                  | 26/20/44.75 in                           | .66/.51/1.14 m | 26/20/44.75 in                           | .66/.51/1.14 m |
| Standard fiberglass                           | 29/26.5/43.5 in                          | .74/.67/1.10 m | 29/26.5/43.5 in                          | .74/.67/1.10 m |
| <b>POWER</b>                                  |  |                |  |                |
| Power source - AC or DC models                | 12V DC / 110/50-60 Hz or 220/50-60 Hz AC |                | 12V DC / 110/50-60 Hz or 220/50-60 Hz AC |                |
| <b>WEIGHT</b>                                 |  |                |  |                |
| AC models (Standard)                          | 1,017 lbs                                | 461 kg         | 1,040 lbs                                | 472 kg         |
| AC models (RT)                                | —  | —              | —  | —              |
| DC models (Standard)                          | 1,107 lbs                                | 502 kg         | 1,130 lbs                                | 513 kg         |
| DC models (RT)                                | —  | —              | —  | —              |
| Air motor (Standard)                          | —  | —              | —  | —              |
| Air motor (RT)                                | —  | —              | —  | —              |



### STANDARDS COMPLIANCE

ANSI A92.3, CSA B354.1, EN 280, AS 1418.10



AERIAL WORK PLATFORMS  
**AWP™ Super Series™**



## Features

### EASILY CONFIGURED TO MEET YOUR NEEDS

#### PLATFORM OPTIONS

- Sliding mid-rail standard platform
- Gated standard platform
- Gated narrow platform
- Standard fiberglass platform

#### POWER OPTIONS

- AC power 85V / 50-60 Hz
- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC 12V with 110V / 230V / 50-60 Hz with worldwide automatic "smart" charging system
- Air motor power 1.5 hp (1.1 kW) (AWP-30 only)

#### BASE OPTIONS

- Standard base
- Rough terrain (RT) base (AWP-20, -25, -30 only)

### OPTIONS & ACCESSORIES

#### PRODUCTIVITY

- Super-straddle
- Gated standard platform
- Gated narrow platform
- Standard fiberglass platform
- Narrow base conversion kit (AWP-20, -25, -30 RT only)
- Operational warning light and descent alarm package
- Tool tray
- Fluorescent tube caddy
- Platform locating laser light

#### POWER

- Air motor power 1.5 hp (1.1 kW) (AWP-30 only)



### STANDARD FEATURES

#### MEASUREMENTS

##### AWP™-20S

- 26 ft 1 in (8.12 m) working height
- 20 ft 1 in (6.12 m) platform height
- 2 ft 5 in (.74 m) standard base width
- 2 ft 6 in (.76 m) RT base width
- Up to 350 lb (159 kg) lift capacity

##### AWP™-25S

- 30 ft 10 in (9.57 m) working height
- 24 ft 10 in (7.57 m) platform height
- 2 ft 5 in (.74 m) standard base width
- 2 ft 6 in (.76 m) RT base width
- Up to 350 lb (159 kg) lift capacity

##### AWP™-30S

- 35 ft 6 in (11.02 m) working height
- 29 ft 6 in (9.02 m) platform height
- 2 ft 5 in (.74 m) standard base width
- 2 ft 6 in (.76 m) RT base width
- Up to 350 lb (159 kg) lift capacity

##### AWP™-36S

- 42 ft 5 in (13.10 m) working height
- 36 ft 5 in (11.10 m) platform height
- 2 ft 5 in (.74 m) standard base width
- Up to 350 lb (159 kg) lift capacity

##### AWP™-40S

- 46 ft 4 in (14.29 m) working height
- 40 ft 4 in (12.29 m) platform height
- 2 ft 5 in (.74 m) standard base width
- Up to 300 lb (136 kg) lift capacity

#### PRODUCTIVITY

- Auxiliary platform lowering
- Most rigid mast in the industry
- Rocker base system for maneuverability
- Tilt back frame (standard on AWP-36, -40)
- Easily rolls through standard doorways
- AC power to platform
- Dual activated up/down switch
- Ground fault interrupt (ANSI / CSA only)
- Small outrigger footprints
- Outrigger storage sockets
- Easy loading in pickup trucks
- Tie down attachment points
- Overhead crane attachment point
- Wide forklift pockets
- Rear access forklift pocket
- LED lights confirm proper set-up

#### POWER

- AC power 85V / 50-60 Hz
- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power 110V / 230V / 50-60 Hz with worldwide automatic "smart" charging system